



**KELVIN (CCT):**

- 2700K 827
- 3000K 830
- 4000K 840



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

**PART NUMBER:**

# FLED13PAR30/8XX/3PK

## LED 13W PAR30

Fusion LED PAR30 3 packs provide a straight-forward and cost effective switch from traditional technologies to LED for over 80% energy savings. Fusion's unique bulk packaging houses 3 individual 13w LED PAR30 lamps in one place making them easy to transport and store.

**FEATURES & BENEFITS:**

- Dimmable
- 90 CRI
- Classic Optic Design
- 75w Replacement
- Rated for Open Fixtures
- Wet Location Rated
- 40° Flood Beam Angle
- Energy Star

**APPLICATIONS:**

- Hotels and Conference Centres
- Offices and Administrative Buildings
- Institutions; Hospital, College/University
- Restaurant, Banquet Hall
- Retail stores and Malls
- Residential; Home, Cottage

**APPROVALS**



**ORDERING INFORMATION:**

PART NUMBER	DESCRIPTION	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED13PAR30/827/3PK	13w PAR30 2700K	8	462 x 412 x 161mm - 18.2 x 16.2 x 6.3"	3.29kg - 7.25lb
FLED13PAR30/830/3PK	13w PAR30 3000K	8	462 x 412 x 161mm - 18.2 x 16.2 x 6.3"	3.29kg - 7.25lb
FLED13PAR30/840/3PK	13w PAR30 4000K	8	462 x 412 x 161mm - 18.2 x 16.2 x 6.3"	3.29kg - 7.25lb

**OPERATING SPECIFICATIONS:**

PART NUMBER	LAMP WATTS	LUMENS	EFFICACY	CCT	CRI	Cert 1	DIMMABLE	RATED LIFE	SUITABLE FIXTURE TYPE	WARRANTY
FLED13PAR30/827/3PK	13W	800 lm	61.5 lm/W	2700K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years
FLED13PAR30/830/3PK	13W	800 lm	61.5 lm/W	3000K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years
FLED13PAR30/840/3PK	13W	800 lm	61.5 lm/W	4000K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years





PART NUMBER:

**FLED13PAR30/8XX/3PK**

LED 13W PAR30

## ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT(mA)	OPERATING FREQUENCY	POWER FACTOR
FLED13PAR30/8XX/3PK	13W	120	112mA	60Hz	> 0.9

## PHYSICAL SPECIFICATIONS:

PART NUMBER	LAMP STYLE	LAMP HOUSING	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	OPERATING TEMP.	STORAGE TEMP.	LED TYPE
FLED13PAR30/8XX/3PK	PAR30	WHITE	E26	117mm - 4.6"	95mm - 3.74"	-20°C / +40°C	-40°C / +85°C	SMD

RoHS  
COMPLIANT

LED

