



## KELVIN (CCT):

2700K 827

3000K 830

4000K 840



## ORDERING INFORMATION:

PART NUMBER	DESCRIPTION	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED19PAR38/827/3PK	19w PAR38 2700K	8	556 x 520 x 182mm - 21.9 x 20.5 x 7.2"	4.97kg - 11lb
FLED19PAR38/830/3PK	19w PAR38 3000K	8	556 x 520 x 182mm - 21.9 x 20.5 x 7.2"	4.97kg - 11lb
FLED19PAR38/840/3PK	19w PAR38 4000K	8	556 x 520 x 182mm - 21.9 x 20.5 x 7.2"	4.97kg - 11lb

## OPERATING SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LUMENS	EFFICACY	CCT	CRI	Cert 1	DIMMABLE	RATED LIFE	SUITABLE FIXTURE TYPE	WARRANTY
FLED19PAR38/827/3PK	19W	1200 lm	61.5 lm/W	2700K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years
FLED19PAR38/830/3PK	19W	1200 lm	61.5 lm/W	3000K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years
FLED19PAR38/840/3PK	19W	1200 lm	61.5 lm/W	4000K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years

PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

## PART NUMBER:

**FLED19PAR38/8XX/3PK****LED 19W PAR38**

Fusion LED PAR38 3 packs provide a straight-forward and cost effective switch from traditional technologies to LED for over 80% energy savings. Fusion's unique bulk packaging houses 3 individual 19w LED PAR38 lamps in one place making them easy to transport and store.

## FEATURES &amp; BENEFITS:

- Dimmable
- 90 CRI
- Classic Optic Design
- 90w Replacement
- Rated for Open Fixtures
- Wet Location Rated
- 40° Flood Beam Angle
- Energy Star

## APPLICATIONS:

- Hotels and Conference Centres
- Offices and Administrative Buildings
- Institutions; Hospital, College/University
- Restaurant, Banquet Hall
- Retail stores and Malls
- Residential; Home, Cottage

## APPROVALS





PART NUMBER:

**FLED19PAR38/8XX/3PK**

LED 19W PAR38

## ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT(mA)	OPERATING FREQUENCY	POWER FACTOR
FLED19PAR38/8XX/3PK	19W	120	157mA	60Hz	> 0.9

## PHYSICAL SPECIFICATIONS:

PART NUMBER	LAMP STYLE	LAMP HOUSING	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	OPERATING TEMP.	STORAGE TEMP.	LED TYPE
FLED19PAR38/8XX/3PK	PAR38	WHITE	E26	130mm - 5.12"	120mm - 4.72"	-20°C / +40°C	-40°C / +85°C	SMD

RoHS  
COMPLIANT

LED

