



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

FLED8.5PAR20/8XX/3PK

LED 8.5W PAR20

Fusion LED PAR20 3 packs provide a straight-forward and cost effective switch from traditional technologies to LED for over 80% energy savings. Fusion's unique bulk packaging houses 3 individual 8.5w LED PAR20 lamps in one place making them easy to transport and store.

FEATURES & BENEFITS:

- Dimmable
- 90 CRI
- Classic Optic Design
- 50w Replacement
- Rated for Open Fixtures
- Wet Location Rated
- 40° Flood Beam Angle
- Energy Star

APPLICATIONS:

- Hotels and Conference Centres
- Offices and Administrative Buildings
- Institutions; Hospital, College/University
- Restaurant, Banquet Hall
- Retail stores and Malls
- Residential; Home, Cottage

APPROVALS



KELVIN (CCT):

- 2700K 827
- 3000K 830
- 4000K 840



ORDERING INFORMATION:

PART NUMBER	DESCRIPTION	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED8.5PAR20/827/3PK	8.5w PAR20 2700K	16	336 x 284 x 222mm - 13.2 x 11.2 x 8.7"	3.65kg - 8.05lb
FLED8.5PAR20/830/3PK	8.5w PAR20 3000K	16	336 x 284 x 222mm - 13.2 x 11.2 x 8.7"	3.65kg - 8.05lb
FLED8.5PAR20/840/3PK	8.5w PAR20 4000K	16	336 x 284 x 222mm - 13.2 x 11.2 x 8.7"	3.65kg - 8.05lb

OPERATING SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LUMENS	EFFICACY	CCT	CRI	Cert 1	DIMMABLE	RATED LIFE	SUITABLE FIXTURE TYPE	WARRANTY
FLED8.5PAR20/827/3PK	8.5W	520 lm	61 lm/W	2700K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years
FLED8.5PAR20/830/3PK	8.5W	520 lm	61 lm/W	3000K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years
FLED8.5PAR20/840/3PK	8.5W	520 lm	61 lm/W	4000K	90	Energy Star	YES	25,000 hrs	OPEN	3 Years



PART NUMBER:

FLED8.5PAR20/8XX/3PK

LED 8.5W PAR20

ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT(mA)	OPERATING FREQUENCY	POWER FACTOR
FLED8.5PAR20/8XX/3PK	8.5W	120	78mA	60Hz	> 0.7

PHYSICAL SPECIFICATIONS:

PART NUMBER	LAMP STYLE	LAMP HOUSING	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	OPERATING TEMP.	STORAGE TEMP.	LED TYPE
FLED8.5PAR20/8XX/3PK	PAR20	WHITE	E26	86mm - 3.4"	63mm - 2.5"	-20°C / +40°C	-40°C / +85°C	SMD



RoHS COMPLIANT



LED

