

PART NUMBER:	DATE:
PROJECT#:	TYPE:
PREPARED BY:	

PART NUMBER:

FLED7PAR20FLD8**/G4

LED 7W PAR20 FLOOD

FUSION's LED PAR16, PAR20 & PAR38, MR16, BR30 & A19 lamps are designed to perform and offer exceptional life, high efficacy, and easy integration within your existing lighting fixtures, making it a simple and cost effective switch. Make your space more energy efficient using Fusion's impressive line of Energy Star qualified LED lamps; brighten your spaces with accented and focussed light, whilst saving money. Bring your space into the 21st century, and light your commercial or residential space with Fusion LED Lamps.

FEATURES & BENEFITS:

- Energy Star Approved & Listed
- 5 Year Warranty
- > 25,000 Hour Long Life Equates To Lower Maintenance Costs
- State of Art Technology
- Design Style
- Industry Standard Lamp Bases
- Dimmable to 5%
- Contains No Mercury or Lead
- Creates Punch & Pizzazz and Visually Appealing Aesthetics
- Targeted And Controlled Light For Better Design
- Low Energy Usage Equates To Benefits For The Environment
- Exceptional Heat Control As A result Of Fusion LED Technology
- · Wet Location Rated

APPLICATIONS:

- Offices Ambient Lighting, Task Lighting, etc.
- Retail Stores Ambient Lighting, Showcase Lighting, etc.
- Restaurants Accent Lighting, Ambient Lighting, atmosphere creation, etc.
- Hotels Accent Lighting, Ambient Lighting, etc.
- Recreational Facilities Accent lighting, Ambient Lighting, etc.

APPROVALS













KELVIN (CCT):

2700K 827

AVAILABLE TYPES:

- 6W PAR16 6W MR16
- 7W PAR20 7W MR16
- 10W PAR30 7W A19
- 15W PAR38 9.5W A19
- 17W PAR38

ORDERING INFORMATION:

PART NUMBER	DESCRIPTION	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED7PAR20FLD827/G4	Fusion LED 7W PAR20 Flood 2700K	12	313 x 236 x 144mm / 12.2 x 9.3 x 5.7"	2.03 KG / 4.5 LB
FLED7PAR20FLD830/G4	Fusion LED 7W PAR20 Flood 3000K	12	314 x 236 x 144mm / 12.2 x 9.3 x 5.7"	2.03 KG / 4.5 LB

OPERATING SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LUMENS	EFFICACY (LPW)	ССТ	CRI	CERT1	CERT2	DIMMABLE	RATED LIFE	WARRANTY
FLED7PAR20FLD827/G4	7W	460 lm	65.7	2700K	90	cULus	EnergyStar	YES	25,000 hrs	5 Years
FLED7PAR20FLD830/G4	7W	470 lm	67.1	3000K	90	cULus	EnergyStar	YES	25,000 hrs	5 Years



PART NUMBER:


FLED7PAR20FLD8**/G4

LED 7W PAR20 FLOOD


ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT (mA)	OPERATING FREQUENCY	POWER FACTOR	DRIVER	MAX THD%
FLED7PAR20FLD827/G4	7W +-10%	120VAC +-10%	70	60 Hz	> 0.7	Integral	58.88
FLED7PAR20FLD830/G4	7W +-10%	120VAC +-10%	70	60 Hz	> 0.7	Integral	58.88


SPECTRAL POWER DISTRIBUTION - 2700K (827)



SPECTRAL POWER DISTRIBUTION - 3000K (830)



LUMINANCE DISTRIBUTION DIAGRAM



PHYSICAL SPECIFICATIONS:

PART	LAMP	BASE	MAX. OVERALL	MAX. OVERALL
NUMBER	STYLE		LENGTH (MOL)	DIAMETER (MOD)
FLED7PAR20FLD8**/G4	PAR20	E26	3.35" (86mm)	2.5" (63mm)

WEIGHT	OPERATING TEMP.	STORAGE TEMP.	
113g / 4.0oz	-40°C - +40°C	-40°C - +40°C	

MOD -

^{*} NOTE: Physical specifications are the same for all colour temperatures

















