

**FUSI**ON



### **PART NUMBER:**

# FLED9.5A198\*\*/10PK

### LED 9.5W A19

Fusion FLED A19 10 packs provide a straight-forward and cost effective switch from traditional technologies to LED for up to 85% energy savings. Fusion's unique bulk packaging houses 10 individual 9W LED 60W replacement lamps in one place making them easy to transport, store and reduce waste to further benefit the environment we share.

### **FEATURES & BENEFITS:**

- 60W Replacement
- Rated for open fixtures
- Long Life 10,000 hours
- Contains no mercury or lead
- Damp location rated
- OMNI Directional Design
- Soft white frost A19 shape with no visible diodes

### **APPLICATIONS:**

- Hotels and Hospitality
- Offices and Administrative Buildings
- Institutions Hospital, College, University
- Residences Home, Cottage
- Storage Facilities
- Senior/Retirement Residences
- Temporary Lighting Contractor String Lighting

# **APPROVALS**





**RoHS** 







## ORDERING INFORMATION:

830

850

KELVIN (CCT):

3000K

4000K

5000K

| PART NUMBER        | DESCRIPTION    | CASE<br>QTY | CASE DIMENSIONS                                 | CASE<br>WEIGHT      |  |
|--------------------|----------------|-------------|---|---------------------|--|
| FLED9.5A19827/10PK | 9.5W A19 2700K | 60          | 21.5 x 13.5 x 5.75" - 546.1 x 342.9 x 146.05 mm | 8.35 lbs - 3.79 kgs |  |
| FLED9.5A19830/10PK | 9.5W A19 3000K | 60          | 21.5 x 13.5 x 5.75" - 546.1 x 342.9 x 146.05 mm | 8.35 lbs - 3.79 kgs |  |
| FLED9.5A19840/10PK | 9.5W A19 4000K | 60          | 21.5 x 13.5 x 5.75" - 546.1 x 342.9 x 146.05 mm | 8.35 lbs - 3.79 kgs |  |
| FLED9.5A19507/10PK | 9.5W A19 5000K | 60          | 21.5 x 13.5 x 5.75" - 546.1 x 342.9 x 146.05 mm | 8.35 lbs - 3.79 kgs |  |

### **OPERATING SPECIFICATIONS:**

| PART NUMBER        | LAMP<br>WATTS | LUMENS | EFFICACY | ССТ   | CRI | Cert 1 | DIMMABLE | RATED<br>LIFE | SUITABLE<br>FIXTURE<br>TYPE | WARRANTY  |
|--------------------|---------------|--------|----------|-------|-----|--------|----------|---------------|-----------------------------|---|
| FLED9.5A19827/10PK | 9.5W          | 750 lm | 79 lm/W  | 2700K | 80  | UL     | NO       | 10,000 hrs    | Open Rated                  | Rated for 10,000<br>hours based on<br>3 hours per day |
| FLED9.5A19830/10PK | 9.5W          | 750 lm | 79 lm/W  | 3000K | 80  | UL     | NO       | 10,000 hrs    | Open Rated                  |   |
| FLED9.5A19840/10PK | 9.5W          | 750 lm | 79 lm/W  | 4000K | 80  | UL     | NO       | 10,000 hrs    | Open Rated                  |   |
| FLED9.5A19850/10PK | 9.5W          | 750 lm | 79 lm/W  | 5000K | 80  | UL     | NO       | 10,000 hrs    | Open Rated                  |   |



PART NUMBER:

# FLED9.5A198\*\*/10PK

LED 9.5W A19

#### **ELECTRICAL SPECIFICATIONS:**

| PART NUMBER        | LAMP<br>WATTS | LAMP<br>Operating voltage | LAMP OPERATING<br>CURRENT(mA) | OPERATING FREQUENCY | POWER FACTOR |  |
|--------------------|---------------|---------------------------|-------------------------------|---------------------|--------------|--|
| FLED9.5A198**/10PK | 9.5W          | 120                       | 95                            | 60Hz                | > 0.6        |  |

#### **PHYSICAL SPECIFICATIONS:**

| PART NUMBER        | LAMP<br>STYLE | BULB<br>FINISH | BASE | MAX OVERALL<br>LENGTH (MOL) | MAX OVERALL<br>DIA. (MOD) | WEIGHT             | OPERATING<br>TEMP. | STORAGE<br>TEMP. | LED<br>TYPE |
|--------------------|---------------|----------------|------|-----------------------------|---------------------------|--------------------|--------------------|------------------|-------------|
| FLED9.5A198**/10PK | A19           | WHITE<br>FROST | E26  | 121 mm -<br>4.76"           | 64mm -<br>2.52"           | 0.148lb -<br>2.4oz | -20°C/45°C         | -40°C/85°C       | SMD         |









