



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

PART NUMBER:

FLED5.5A19OMNI840/G7

LED 5.5W OMNI Directional A19

Fusion FLED A19 lamps are designed for high performance and offer an incredibly long life expectancy, high efficacy, and easy integration within your existing light fixtures making for a simple and cost effective switch.

FEATURES & BENEFITS:

- Enclosed Fixture Rated
- Long life - 15,000Hr
- Dimmable to 5% for design flexibility
- Contains no mercury or lead
- Damp location rated
- ENERGY STAR certified
- OMNI Directional Design
- White frost A19 shape envelope with no visible diodes

APPLICATIONS:

- Offices, Schools and Commercial Buildings
- Malls and Retail Stores
- Hotels and Leisure
- Sports and Recreational Facilities
- Home and Cottage

APPROVALS



KELVIN (CCT):

4000K 840

ORDERING INFORMATION:

PART NUMBER	DESCRIPTION	CASE QTY	CASE DIMENSIONS	CASE WEIGHT
FLED5.5A19OMNI840/G7	5.5W A19 4000K OMNI	60	412 x 345 x 278mm - 16.2 x 13.6 x 10.9"	6.4kg - 14.11lb

OPERATING SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LUMENS	EFFICACY	CCT	CRI	Cert 1	Cert 2	Cert 3	DIMMABLE	RATED LIFE	WARRANTY
FLED5.5A19OMNI840/G7	5.5W	450 lm	81.0 lm/W	4000K	80	cULus	FCC	Energy Star	YES	15,000 hrs	3 Years



PART NUMBER:

FLED5.5A190MNI840/G7

LED 5.5W OMNI Directional A19

ELECTRICAL SPECIFICATIONS:

PART NUMBER	LAMP WATTS	LAMP OPERATING VOLTAGE	LAMP OPERATING CURRENT(mA)	OPERATING FREQUENCY	POWER FACTOR
FLED5.5A190MNI840/G7	5.5W	120	95	60Hz	> 0.7

PHYSICAL SPECIFICATIONS:

PART NUMBER	LAMP STYLE	BULB FINISH	BASE	MAX OVERALL LENGTH (MOL)	MAX OVERALL DIA. (MOD)	WEIGHT	OPERATING TEMP.	STORAGE TEMP.	LED TYPE	BEAM ANGLE
FLED5.5A190MNI840/G7	A19	LED	E26	121mm - 4.76"	64mm - 2.52"	0.148lb - 2.4oz	-20°C / 45°C	-40°C / 85°C	SMD	230

